

KEYCOTE® WETTING AGENT

A nonionic surfactant used exclusively in Keycote® system based slurries so the slurry will coat the wax or previously applied shell coat.

Typical Material Properties*

pH (5% in DW)	3-6
Specific Gravity	1.05
Solubility	Soluble in Water

*These results are based on the testing methods, frequency and procedures of Ransom & Randolph or its approved suppliers. The levels referenced herein are only for general guidance and do not constitute a firm specification.

Application Recommendations

Keycote System Slurry**	5 ml/gallon of slurry
-------------------------	-----------------------

**Keycote wetting agent should only be added to a Keycote system slurry. It should only be used to adjust/enhance the wetting capability when needed and does not need to be added to a new slurry. Contact the R&R technical department before using.

As the conditions or methods of use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for any use of this product. Information contained herein is believed to be true and accurate but all statements or suggestions are made without warranty, expressed or implied, regarding accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof. Compliance with all applicable federal, state, and local regulations remains the responsibility of the user. All potential liability related to the sale and use of this product is limited to the cost of the particular goods sold in their respective transactions.



RANSOM & RANDOLPH

3535 Briarfield Boulevard | Maumee, OH 43537 USA
800.800.7496 | 419.865.9497 | 419.865.9997 (FAX) | www.ransom-randolph.com



Issue Date: July 26, 2023

Investing with Innovation™